



Engineering Data

7539 2 WIRE LOW PROFILE VIDEO MONITOR

The Elvox® 7539 monitors are designed to meet any requirement for video intercom security. Unique capacitive touch screen controls are programmable for use as door release, ring tone mute, camera activation, station to station calling and more. Ring tone selection and level control is provided. The 7539 has a special mirror gloss finish. An apartment doorbell input is provided and different ring tones can be selected for an intercom call and a doorbell call. The ultra low profile hands free design is only 25mm. Separate input and output terminals and dip switch termination are provided for ease of installation.

General Information	Specifications
<ul style="list-style-type: none"> ◆ Ultra Low Profile Design ◆ 3.5" LCD High Resolution ◆ Twisted Pair Operation ◆ Private Conversation ◆ Tone Ring Signal ◆ Duplex Voice Operation ◆ Capacitive Touch Screen Controls ◆ Unique Mirror Gloss Finish ◆ Doorbell Input with Distinct Tone ◆ Easy to Install and Program 	<p>System: 2 Wire Video</p> <p>Controls: Capacitive door release, Self activation, Auxiliary Function, 4 extra programmable capacitive controls. Ring tone selection and level</p> <p>Handset: Duplex Handset with electret Mic and heavy duty coiled cord</p> <p>Construction: Moulded High Impact Plastic with mirror gloss finish white or black (7539/04)</p> <p>Terminations: Screw Terminal</p> <p>Dimensions: 131mm W x 150mm H x 25mm D</p> <p>Net Weight: 0.5 Kg</p>

2 Wire Low Profile Video Monitor
7539

Architects and Engineers Specification

The Elvox® 7539 monitors shall be designed to meet any requirement for video intercom security. Unique capacitive touch screen controls are programmable for use as door release, ring tone mute, camera activation, station to station calling and more shall be provided. Ringtone selection and level control shall be provided. The 7539 shall have a special mirror gloss finish. An apartment doorbell input shall be provided and different ring tones can be selected for an intercom call and a doorbell call. The ultra low profile hands free design shall be only 25mm. Separate input and output terminals and dip switch termination are provided for ease of installation. The model 7539 (7539/04) is specified.

7539 Series

Rev 1.0

Form ED7539



RAYTEL SECURITY SYSTEMS

www.raytelsecurity.co.uk

Info@raytelsecurity.co.uk

Southern Office:
Tel: 01268 749310
Fax: 01268 749315

Northern Office:
Tel: 0141 332 4232
Fax: 0141 332 6952